



- Tank is stainless steel AISI 304 and comply with potable water
- Heavy-Duty Chassis: axles with electric brakes and all necessary wiring, full lighting
- Adjustable height of the lunette eye to towing vehicle either to change the location of lunette eye min: 890mm max. 1150mm.
- Lockable waterproof tool box with tire changing tools and lifting jack.
- Retractable wheeled landing leg/jack, to support the front of the fully loaded trailer when not connected to the prime mover. Landing leg/jack is adjustable to facilitate connection to prime movers with pintle heights ranging from 89cm to 115cm.
- Drawbar safety chains capable of securing the trailer to the prime mover in the event of pintle/lunette failure
- Air service brakes with breakaway system
- Glad-hands, in accordance with Sae j318
- Manually activated parking brake, the parking brake can hold the fully loaded trailer on a dry, hard surfaced 30% grade while uncoupled from the towing vehicle
- Electrical system: 12 volt system with Sae j560 7 pins connector
- Tires: tubeless on/off road radial tires
- Two potable water hoses, minimum length 10 foot (3 m) each

DEFINITION

• Name	: Potable water trailer
• Model	: WT- G6001
• Payload	: 2000 Liters
• Load	: Potable Water
• Track	: 1710mm
• Total Weight	: 2980kg
• Size of Tires	: 11 R 22,5mm
• Overall Dimensions	: 3730x2020x1940mm
• Ground Clearance	: 46cm

